



## PRIORITY DOCUMENT TRANSMITTAL FORM

First Named Inventor	Michael Pong Kei Wong
Title	Electrical Adapter
Serial No.	10/749,964
Filing Date	December 31, 2003
Date Allowed	
Examiner	
Group Art Unit	
Attorney Docket Number	MCHK/148/US
Date	February 20, 2004

Mail Stop Document Services  
Director of the United States Patent  
and Trademark Office  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

Sir:


### SUBMISSION OF PRIORITY DOCUMENT

Applicant claims priority from Application No. 0300098.1 filed January 3, 2003 in the United Kingdom. A certified copy of the priority application is enclosed.

Respectfully Submitted,

Michael Pong Kei Wong

By:

  
Guy D. Yale  
Registration No. 29,125  
Alix, Yale & Ristas, LLP  
Attorney for Applicant

Date: February 20, 2004  
750 Main Street, Suite 1400  
Hartford, CT 06103-2721  
(860) 527-9211  
Our Ref: MCHK/148/US

### CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited on the date below with the United States Postal Service as first class mail in an envelope addressed to "Mail Stop Document Services, Director of the United States Patent and Trademark Office, P.O. Box 1450, Alexandria, Virginia 22313-1450."

Typed or Printed Name

Guy D. Yale

Reg. No.

29,125

Signature

Date:

February 20, 2004





INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed 

Dated 7 January 2004



100

100

100

100

100



-----

-----

-----

-----

-----

-----

-----

**Patents Form 1/77**

Patents Act 1977  
(Rule 16)

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference **GBP87367**
2. Patent application number  
(The Patent Office will fill in this part)
3. Full name, address and postcode of the or of each applicant (underline all surnames)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention **Electrical adaptor**

5. Name of your agent (if you have one)  
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application


8. Is a statement of inventorship and of right to grant of a patent

required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

The  
Patent  
Office




06JAN03 E774637-3 002999  
P01/7700 0.00-0300098.1

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

**0300098.1**

Modern Sense Ltd,  
Flat B, 2/F., Hop Lung Factory Building  
1 Mong Lung Street  
Shaukiwan  
Hong Kong



7516776001

Marks & Clerk  
57 - 60 Lincolns Inn fields  
London WC2A 3LS

18001 ✓

Country

Priority application No  
(if you know it)

Date of filing  
(day / month / year)

Number of earlier application

Date of filing  
(day / month / year)

Yes

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form 0

Description 9

Claim(s) 3

Abstract 1

Drawing(s) 5 + 5

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

M. B. + C. L.

Date: 3 January 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

GB Patent Filings  
0207 400 3000

Electrical Adapter

Background of the Invention

5 The present invention relates to main power electrical connectors. More particularly, although not exclusively, the invention relates to a main power electrical adapter having a choice of configurations.

10 Electric plugs for insertion to wall sockets are of course known. These either comprise two or three pins, depending upon whether an earth pin is needed. The plugs have a power cord extending therefrom, usually directly outwardly from the wall, or otherwise in a direction

15 parallel to the wall in a downward or downward and angularly-offset manner. Sometimes this pre-set angle at which the power cord extends from the plug body is inconvenient. For example, when the cord extends normally to the wall and it is desired to place furniture

20 against the wall at that position, the furniture must often need to be spaced from the wall. If the power cord is short and extends downwardly from the plug when the plug is inserted into the wall socket, this can create problems where say it extends from a desk lamp for

25 example to be positioned at a higher level than that of the wall socket. In such a situation, it would be more appropriate that the plug have the power cord extending upwardly instead of downwardly therefrom.

Also, the pin configuration of wall sockets and electrical plugs vary from country to country. When travelling with a laptop computer for example one often  
5 has to carry traveller's adapters. These can be bulky, cumbersome items.

#### Objects of the Invention

10 It is an object of the present invention to overcome or substantially ameliorate at least one of the above disadvantages and/or more generally to provide an improved electrical adapter.

#### 15 Disclosure of the Invention

There is disclosed herein an electrical adapter comprising:

a base having electrical terminals and engagable  
20 pivot connection features, and

a body having engager pivot connecting features for co-operating with the engagable pivot connection features of the base to secure the body rotatably to the base, the body having electrical contacts configured to engage with  
25 the terminals of the base when the body and base are so secured.



Preferably the base has conducting pins extending from one side thereof for insertion into apertures of a mating socket and the electrical terminals are located on the other side of the base and correspond to each of the  
5 conducting pins and are connected electrically thereto.

Alternatively the base can have extending therefrom another power cord at a remote end of which there is a plug having conducting pins for insertion into apertures  
10 of a mating socket and wherein the electrical terminals are connected electrically to each of the conducting pins via individual conductors in said another power cord.

Preferably the engagable and engager pivot mounting  
15 features are mutually bayonet-inter-engagable.

Preferably the engagable pivot mounting features of the base comprise a number of radially extending lugs having circumferentially extending ramp surfaces.  
20

Preferably the engager pivot mounting features of the body comprise openings through which the lugs must pass for interengagement of the base and the body to take place.

25 Preferably said lugs are of differing size and said openings are of corresponding differing size to restrict allowable alignment orientations of the body and base when interconnected.

Preferably the base comprises an annular channel within which the terminals are located.

- 5 Preferably the terminals are located within narrowed parts of the channel.

Preferably the body includes a locking device by which the base is locked to the body when interconnected therewith.

10

Preferably the electrical contacts of the body are spring-biased toward the terminals.

- Preferably the electrical contacts of the body are  
15 connected to individual conductors of a power cord extending from the body.

#### Brief Description of the Drawings

- 20 A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings, wherein:

Figure 1 is a schematic perspective illustration of the  
25 base,

Figure 2 is a schematic inverted perspective illustration of the base,

Figure 3 is a schematic perspective illustration of a body for connection to the base of Figures 1 and 2,

5 Figure 4 is a schematic perspective detailed illustration of parts of the body of Figure 3,

Figures 5 and 6 are schematic perspective illustrations of the body and base showing the base in its alternative  
10 insertion orientations,

Figures 7 and 8 are schematic perspective illustrations of the body and base with the base illustrated in alternate locked orientations, and  
15

Figure 9 is a schematic perspective illustration of an alternative base having an extension cord extending therefrom with a plug at its remote end.

20 Description of the Preferred Embodiment

In the accompanying drawings there is schematically depicted an adapter base 10 and a mating plug body 20.

25 Figures 1 and 2 depict the adapter base 10. The adapter base 10 is fabricated typically as a moulding of plastics material and includes a plate 13 having three projecting metallic electrically conductive pins projecting from one

side. There are active and neutral pins 11 and an earth pin 12. Alternatively, there might simply be a pair of active and neutral pins. As yet a further alternative, the pin 12 might be a plastics or other non-conductive dummy pin. The adapter base 10 of the illustrated embodiment has its pins configured in the standard British layout, but it should be appreciated that the pin configuration could equally be that of Australia, the USA, or any other country. Indeed, the plug body 20 of Figures 3 and 4 might be supplied with a number of bases 10, each base having a configuration applicable for a different country.

At the other side of the plate 13 there is provided a flat bearing ring 14 formed as an integral moulding therewith. Located internally and concentrically with the bearing surface 14 is an inner circular projecting rail 7 and an outer circular rail 15. Between the two rails there is defined an annular channel 9 having a pair of diametrically opposed narrowed portions 8. At the bottom part of each narrowed portion 8 there is provided a terminal 17. One of the terminals is connected electrically with either the active or neutral pin 11 and the other terminal is connected to the other pin 11. There might also be a further terminal 17 connected with the earth pin 12.

The outer rail 15 has extending therefrom four bayonet

lugs 16. Each bayonet lug 16 is spaced from the bearing surface 14 and includes a circumferentially extending ramped upper surface. Diametrically opposed pairs of the bayonet lugs 16 are of the same size, yet adjacent pairs of the bayonet lugs are of differing size.

Figures 3 and 4 depict a plug body 20 for bayonet-inter-connection with the adapter base 10. The plug body 20 is typically fabricated from several plastics moulded parts that are screwed, snapped or welded together ultrasonically and has extending from it via a rubber grommet 22 a power cord 21.

The plug body 20 includes a flat circular bearing ring 33 for engagement with the bearing ring 14 of the adapter base 10. There is a central recess 32 in which there is located a pair of diametrically opposed electrical spring contacts 26. These spring contacts are connected electrically with individual conductors within the cord 21. Located around the central recess 32 there are four openings 31. Diametrically opposed pairs of the openings 31 are of the same size, whereas adjacent pairs are of different size. By this arrangement, bayonet lugs of the adapter base 10 can be lowered into the openings 31 of the plug body 20 in only two possible orientations, namely those as depicted in Figures 5 and 6 respectively. That is, the openings 31 are just large enough to receive the lugs and the larger pair of the four lugs will not

fit into the smaller openings.

Alongside each opening 31 and situated beneath the bearing ring 33 are lug-receiving slots 29. There are  
5 ramp surfaces at the bottom of each opening 31.

Situated alongside and projecting within one of the openings 31 is a locking device comprising an interlock tongue 24 and an activator 23 formed integrally  
10 therewith. The tongue 24 projects into a tongue recess 25 as depicted in Figure 4. With reference again to Figure 1, the outer rail 15 includes a pair of diametrically opposed interlock recesses 18 into one of which the tongue 24 snap-engages upon bayonet-fitting of  
15 the two components. The activator 23 is an integral part of the plug body 20 and has a pair of cut-outs at either side enabling downward movement of the interlocked tongue 24 upon application of finger-pressure to the activator 23. It is only upon this application of finger pressure  
20 that the interlocked parts can be detached.

In use, parts 10 and 20 are attached as shown in Figure 5 and 6 and then the adapter based 10 is rotated clockwise until the bayonet lugs bear against end walls 28 at each  
25 slot 29. At this time, the interlock tongue 24 snaps into one of the interlock recesses 18, depending upon the chosen orientation as depicted in either of Figures 7 or 8. The attached components can then be plugged into a

wall socket, plug board, or extension cord for example.

There is an alignment indicator 30 on the plug body 20 and a corresponding pair of indicators 34 on the adapter base to assist in aligning the components as illustrated in Figures 5 and 6.

It should be appreciated that modifications and alterations obvious to those skilled in the art are not to be considered as beyond the scope of the present invention. For example, there might be located within the plug body 20 a transformer to provide a low voltage output to the power cord 21. Also, instead of a bayonet-type interengagement, other types of plug-in arrangements might be adopted.

Furthermore, it is envisaged that the base of the electrical adapter need not be configured with pins to be received directly by apertures of a mating socket. For example, and as shown in Figure 9, the base might have an extension cord 35 extending therefrom and at the remote end of which there is a standard plug 36 to be received by a wall socket or another extension cord for example.

25

Also, the body might be formed integrally with an electrical appliance, double adapter, multiple plug board, transformer box or the like.

CLAIMS:

1. An electrical adapter comprising:  
a base having electrical terminals and engagable  
5 pivot connection features, and  
a body having engager pivot connecting features for  
co-operating with the engagable pivot connection features  
of the base to secure the body rotatably to the base, the  
body having electrical contacts configured to engage with  
10 the terminals of the base when the body and base are so  
secured.
2. The electrical adapter of Claim 1 wherein the base  
has conducting pins extending from one side thereof for  
15 insertion into apertures of a mating socket and the  
electrical terminals are located on the other side of the  
base and correspond to each of the conducting pins and are  
connected electrically thereto.
- 20 3. The electrical adapter of Claim 1 wherein the base  
has extending therefrom a power cord at a remote end of  
which there is a plug having conducting pins for insertion  
into apertures of a mating socket and wherein the  
electrical terminals are connected electrically to each of  
25 the conducting pins via individual conductors in the power  
cord.
4. The electrical connector of Claim 1, wherein the



engagable and engager pivot mounting features are mutually bayonet-inter-engagable.

5. The electrical connector of Claim 1, wherein the  
5 engagable pivot mounting features of the base comprise a number of radially extending lugs having circumferentially extending ramp surfaces.

6. The electrical connector of Claim 1 wherein the  
10 engager pivot mounting features of the body comprise openings through which the lugs must pass for interengagement of the base and the body to take place.

7. The electrical connector of Claim 6 wherein said lugs  
15 are of differing size and said openings are of corresponding differing size to restrict allowable alignment orientations of the body and base when interconnected.

8. The electrical connector of Claim 1 wherein the base  
20 comprises an annular channel within which the terminals are located.

9. The electrical connector of Claim 8 wherein the  
25 terminals are located within narrowed parts of the channel.

10. The electrical connector of Claim 1 wherein the body

includes a locking device by which the base is locked to the body when interconnected therewith.

11. The electrical connector of Claim 1 wherein the  
5 electrical contacts of the body are spring-biased toward the terminals.

12. The electrical connector of Claim 1 wherein the body  
is integrated into an electrical appliance, double  
10 adapter, multiple plug board, transformer box or the like.

13. The electrical connector of Claim 1 wherein the  
electrical contacts of the body are connected to  
15 individual conductors of a power cord extending from the body.

Electrical Adapter

ABSTRACT

5 An electrical adapter includes a base having conducting pins extending from one side for insertion into apertures of a mating socket, electrical terminals on the other side and electrically connected to each of the conducting pins. The base a bayonet fitting. A body for connection to the  
10 base has a corresponding bayonet fitting for co-operating with the bayonet fitting of the base to secure the body to the base in a desired orientation. There are electrical contacts configured on the body to engage with the terminals of the base when the body and base are secured  
15 to one another. A power cord extends from the body.



11 12



-----

1/5

10




FIGURE 1

10




FIGURE 2



11 11



-----

-----

1

1

1




FIGURE 3




FIGURE 4



11 2



-----






FIGURE 5




FIGURE 6



11 4



-----

4/5




FIGURE 7




FIGURE 8



11 12 13



-----

-----

1

2

3

4




FIGURE 9



0. 1. 2.



2

3

4

5

6

7

8